

Projectors up to Native 4K for installation, rental and staging



Model	EB-L510U	EB-L610U EB-L615U	EB-L1050U	EB-L1070U / EB-L1075U	EB-L1490U / EB-L1495U	EB-L1500UH / EB-L1505UH	EB-L1750U / EB-L1755U	L12000Q/ L12002Q	EB-L20000U / EB-L20002U	EB-L30000U/ EB-L30002U
Colour Light Output (lumens) normal / eco	5000 / 3500	6000 / 4200	5500 / 3850	7000 / 4900	9000 / 6300	12000 / 8400	15000 / 10500	12000 / 8400	20000 / 14000	30000 / 20000
Resolution	WUXGA	WUXGA	WUXGA / 4K-Enhancement	WUXGA / 4K-Enhancement	WUXGA / 4K-Enhancement	WUXGA / 4K-Enhancement	WUXGA / 4K-Enhancement	Native 4K	WUXGA	WUXGA / 4K-Enhancement
Noise (dB) normal / eco	37 / 25	38 / 27	34 / 30	36 / 30	37 / 30	37 / 30	40 / 30	45 / 38	45 / 38	49 / 41
Throw ratio in native aspect	1.35:1 - 2.20:1	1.35:1 - 2.20:1	1.42 - 2.28:1 ¹	1.42 - 2.28:1 ¹	1.57:1 - 2.56:1 ²	1.57:1 - 2.56:1 ²	1.57:1 - 2.56:1 ²	1.52 - 2.47:1 ³	1.57 - 2.56:1 ³	1.74:1 - 2.35:1 ⁴
Dimensions (W x D x H mm)	440 x 304 x 120	440 x 304 x 120	545 x 436 x 189	545 x 436 x 189	582 x 492 x 211	582 x 492 x 211	586 x 492 x 211	790 x 620 x 358	790 x 620 x 358	790 x 710 x 299
Weight (Kg)	8.5	8.5	16.9	16.9	23.7	23.8	24.1	51.4	49.6	69.9
Power consumption normal / eco (W)	322 / 244	353 / 265	345 / 252	416 / 299	626 / 512	908 / 597	1024 / 647	1741 / 1030	1860 / 1123	2325 / 1511



¹ With ELPLM08 - not supplied. ² With supplied standard lens. ³ With ELPLM15 - not supplied. ⁴ With ELPLM12 - not supplied.

⁵ 2001 to 2019, 500-lumen and above, excluding screenless TVs, Futuresource Consulting – Quarterly Projector Market Insights – Worldwide Analyzer CY20Q1.

⁶ Special order only.

Lens options for installation, rental and staging



Model	ELPLX03	ELPLR05	ELPLU05	ELPLW07	ELPLM12	ELPLM13	ELPLM14	ELPLL09	ELPLL10
EB-L30000U	Ratio: 0.34:1	Ratio: 0.63:1	Ratio: 0.90 - 1.09:1	Ratio: 1.29 - 1.76:1	Ratio: 1.74 - 2.35:1	Ratio: 2.28 - 3.46:1	Ratio: 3.41 - 5.12:1	Ratio: 4.79 - 7.20:1	Ratio: 6.96 - 10.45:1
Lens shift V / H	+ 25% / ± 15%	± 15% / ± 5%	± 55% / ± 25%	± 65% / ± 30%	± 65% / ± 30%	± 65% / ± 30%	± 65% / ± 30%	± 55% / ± 25%	± 55% / ± 25%



Model	ELPLX01W / ELPLX01	ELPLX02W / ELPLX02	ELPLU03S	ELPLU04	ELPLW05*	ELPLW08	ELPLW06	ELPLM08	ELPLM15	ELPLM10	ELPLM11	ELPLL08
EB-L1050U through to EB-L1075U	Ratio: 0.35:1	—	Ratio: 0.65 - 0.78:1	Ratio: 0.87 - 1.05:1	Ratio: 1.04 - 1.46:1	Ratio: 1.18 - 1.66:1	—	Ratio: 1.42 - 2.28:1	Ratio: 2.16 - 3.48:1	Ratio: 3.32 - 5.06:1	Ratio: 4.85 - 7.38:1	Ratio: 7.21 - 10.11:1
Lens shift V / H	+ 17% / ± 10%	—	± 67% / ± 30%	± 67% / ± 30%	± 67% / ± 30%	± 67% / ± 30%	—	± 67% / ± 30%	± 67% / ± 30%	± 67% / ± 30%	± 67% / ± 30%	± 67% / ± 30%
EB-L1490U through to EB-L20000U**	—	Ratio: 0.35:1	Ratio: 0.48 - 0.57:1	Ratio: 0.64 - 0.77:1	Ratio: 0.77 - 1.07:1	Ratio: 0.86 - 1.2:1	Ratio: 1.19 - 1.62:1	—	Ratio: 1.57 - 2.56:1	Ratio: 2.42 - 3.71:1	Ratio: 3.54 - 5.41:1	Ratio: 5.27 - 7.41:1
Lens shift V / H	—	+ 25% / ± 15%	+ 24% / ± 10%	± 60 / ± 18%	± 24% / ± 10%	± 60% / ± 18%	± 60% / ± 18%	—	± 60% / ± 18%	± 60% / ± 18%	± 60% / ± 18%	± 60% / ± 18%
EB-L12000Q	—	Ratio: 0.34:1	Ratio: 0.46 - 0.56:1	Ratio: 0.62 - 0.75:1	Ratio: 0.74 - 1.04:1	Ratio: 0.83 - 1.17:1	Ratio: 1.15 - 1.57:1	—	Ratio: 1.52 - 2.47:1	Ratio: 2.34 - 3.59:1	Ratio: 3.42 - 5.23:1	Ratio: 5.09 - 7.16:1
Lens shift V / H	—	+ 23% / ± 10%	± 18% / ± 6%	± 58 / ± 16%	± 18% / ± 6%	± 58% / ± 16%	± 58% / ± 16%	—	± 58% / ± 16%	± 58% / ± 16%	± 58% / ± 16%	± 58% / ± 16%

*ELPLW05 brightness is limited to maximum 12,000 lumens. **This applies to WUXGA resolutions - data varies for other resolutions

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners. Product information is subject to change without prior notice.